

SPECIFICATION
SILENT GLISS SYSTEM
#6370 CORD DRAWN DRAPERY TRACK

Part 1 - General

1.01 SUMMARY

- A. Work of this section includes manual window treatment / stage hardware as manufactured by Silent Gliss USA, Inc.

1.02 SUBMITTALS

- A. Product data: Manufacturer's descriptive literature shall be submitted, indicating materials, finishes and installation instructions for each type of window treatment specified.
- B. Shop drawings: Wiring diagrams for any electrical components and installation detail drawings shall be supplied as requested.

1.03 QUALITY ASSURANCE

- A. Products shall be manufactured to meet or exceed all quality standards as stipulated in the Quality Control Manual, issued by Silent Gliss.

1.04 DELIVERY, STORAGE AND HANDLING

- A. Product shall be delivered to the project site in manufacturer's original packaging.
- B. Product shall be handled and stored to prevent damage to materials, finishes and operating mechanisms.

1.05 WARRANTY

- A. Manufacturer shall provide that all system components are free of defects for Five years from the date of installation. Specific product warranty terms are available from Silent Gliss.

Part 2 - Product

2.01 MANUFACTURER

- A. Acceptable product: Window treatment system, #6370 CORD DRAWN DRAPERY TRACK as manufactured by Silent Gliss USA, Inc. PO Box 405, Loganville, Georgia 30052

2.02 EQUIPMENT

- A. Heavy duty or stage, cord drawn drapery track. Specifically designed with dual channels permitting unlimited overlapping of draperies using one system.

2.03 COMPONENTS

- A. Track:
 - 1. Shall be 6063-T6 clear anodized aluminum, curvable on both inside and outside radii, to a minimum radius of 20".
 - 2. Shall have enclosed cord channels which will prevent cords from falling out of the system.
 - 3. Shall have exterior dimensions of 1" height x 1-3/4" width.
- B. Parts:
 - 1. All parts shall be made of polyamid 6,6, Delrin, stainless steel or galvanized steel.
 - 2. System shall include 4 #6098 rollers per foot and shall be ceiling mounted with appropriate screws, directly through the center of the headrail or wall mounted with #3239 brackets at approx. 24" o.c.
 - 3. Shall be original Silent Gliss components.

Part 3 - Execution

3.01 INSTALLATION

- A. Install window treatment system in accordance with Silent Gliss specifications, standards and procedures. Installation contractor shall be responsible for site measurements and suitability of mounting surface.
- B. Adequate clearance shall be provided to permit unencumbered operation of the entire system.

