

**SPECIFICATION
SILENT GLISS
#3840 CORD DRAWN SKYLIGHT SYSTEM**

Part 1 - General

1.01 SUMMARY

- A. Work of this section includes manual window treatment hardware as manufactured by Silent Gliss USA, Inc.

1.02 SUBMITTALS

- A. Product data: Manufacturer's descriptive literature shall be submitted, indicating materials, finishes and installation instructions for each type of window treatment specified.
- B. Shop drawings: Wiring diagrams for any electrical components and installation detail drawings shall be supplied as requested.

1.03 QUALITY ASSURANCE

- A. Products shall be manufactured to meet or exceed all quality standards as stipulated in the Quality Control Manual, issued by Silent Gliss.

1.04 DELIVERY, STORAGE AND HANDLING

- A. Product shall be delivered to the project site in manufacturer's original packaging.
- B. Product shall be handled and stored to prevent damage to materials, finishes and operating mechanisms.

1.05 WARRANTY

- A. Manufacturer shall provide that all system components are free of defects for Five years from the date of installation. Specific product warranty terms are available from Silent Gliss.

Part 2 - Product

2.01 MANUFACTURER

- A. Acceptable product: Window treatment, #3840 CORD DRAWN SKYLIGHT SYSTEM as manufactured by Silent Gliss USA, Inc. PO Box 405, Loganville, Georgia 30052

2.02 EQUIPMENT

- A. Light duty, cord operated skylight hardware system suitable for horizontal applications.

2.03 COMPONENTS

- A. Track:
 - 1. Shall be 6063-T6 clear anodized aluminum.
 - 2. Shall have two separate, internal cord channels.
 - 3. Shall have exterior dimensions of 15/16" height x 7/8" width.
- B. Parts:
 - 1. All parts shall be made of polyamid 6.6, Delrin, stainless steel or galvanized steel.
 - 2. System shall include #6146 / 2507 roller carriers, 1 #3845 cord pulley, 2 #3846 corner guides and shall be ceiling mounted with #3825 swing clamps at approximately 22" o.c.
 - 3. System shall also include #2011 / 2012 cross tubes spaced at approximately 12" o.c.
 - 4. Shall be original Silent Gliss components.

Part 3 - Execution

3.01 INSTALLATION

- A. Install window treatment system in accordance with Silent Gliss specifications, standards and procedures. Installation contractor shall be responsible for site measurements and suitability of mounting surface.
- B. Adequate clearance shall be provided to permit unencumbered operation of the entire system.

